

MOTT GAS PURIFIERS HIGH PURITY BULK SERIES



Mott Helium Gas Bulk Purifier System (Model HP6-R-G)

Feature Overview

- Fully Automated PLC Controls with HMI (Human Machine Interface)
- Rare Gas Getter Purifier
- Electric Gas Preheaters with Closed-Loop Temperature Controls
- Alarm Relay / Remote Contact Shutdown / Gas Relay
- All Metal Enclosure with Doors
- Impurities Removed to < 1 ppb: H₂O, CH₄, CO, CO₂, O₂, H₂, N₂

Included Features

- Inlet & Outlet Isolation Valves
- Inlet Mass Flow Meter (4-20mA Output)
- Inlet & Outlet Pressure Transducers (4-20mA Output)
- High Temperature Hardware Interlock
- Auto or Manual Bypass
- Over Pressurization Safety System
- Integrated Particle Filtration
- MODBUS Data Communication Port
- Ground Fault Protection (GFI)
- Emergency Off Button (EMO)
- Separate Control Power
- Purifier Hold Down Brackets & Lifting Points
- Uninterruptible Power Supply (UPS)
- ASME Stamp/CE Marking (must be specified on order)

Purifier Specifications

- **Dimensions:** 180cm x 80 cm x 61 cm (H x L x W)
- **Weight:** < 400Kg
- **Clearance Required:** 1 meter on all sides
- **Inlet & Outlet Connections:** 1/2" FVCR
- **Instrument Air Connection:** 3/8" Compression
- **Burst Disk Pressure:** 13.8 barg (Customizable)
- **Integrated Particle Filtration:** 0.003µm (3nm)
- **Wetted Surface Finish:** 316L SS, EP 12Ra Maximum

Purifier Specifications

Max Flow Rate	6 Nm ³ /hr
Min Flow Rate	0.6 Nm ³ /hr
Inlet Pressure (min-max)	4.1 - 17.2 barg
Max Pressure Drop @ 6.9 barg	< 0.7 bard (standard)
Inlet Gas Temp(min-max)	0° - 35°C
Outlet Gas Temp	Ambient



Control System Details

- Control & Display Interface
- Automatic Alarm Response & Display (Including Valve Operation)
- System Temperatures
- Heater Power Levels
- Optional Gas Pressure Readouts
- Warning and Alarm Status and Optional Gas Flow
- Totalizer Readout

MOTT GAS PURIFIERS HIGH PURITY BULK SERIES



Mott He Gas Purifier Proposal

Customer:

End User:

Working Gas:

Impurity	Inlet	Mott Purifier Outlet
O ₂	≤ 2 ppm	≤ 1 ppbv
N ₂	≤ 3 ppm	≤ 1 ppbv
H ₂ O	≤ 3 ppm	≤ 1 ppbv
Hydrocarbons	≤ 0.2 ppm	≤ 1 ppbv
CO	Not specified	Not specified**
H ₂	Not specified	Not specified**
CO ₂	Not specified	Not specified**
CH ₄	Not specified	Not specified**
Particles	Not specified	Integrated 1.5nm Filter

**Mott can calculate outlet specifications if inlet specs are provided

Facilities Requirements:

- **Main Power:** 208 VAC, 1 Phase, 50/60 Hz – 2 kW
- **Control Power:** 110 or 220 VAC, 1 Phase, 50/60 Hz – 100 W
- **Average Power at Max Flow:** 0.3 kW
- **Instrument Air:** 6.6 – 9.7 barg
- **Indoor Temperature:** 5° - 35°C

Additional Details and Specifications

General Purifier Specifications			
Height	Length	Width	Weight
< 180 cm	~80 cm	~61 cm	< 400 kg
Instrument Air Inlet		Process Gas Pressure Relief	
3/8 in FNPT		1/4 in Tube Stub	